

EKAER Management Service

Contents

- 1 Introduction 5
 - 1.1 Objective

1 INTRODUCTION

2 STRUCTURE OF OPERAT

of the request.

The secret signature key of testekek used in the example (set by the user on the WEB interface):
Elek65Titkos

Data of the example request:

The tradeCard element

		and D yes)	the Hungarian tax registration number. In case of a foreign sender, the community tax registration number.	
sellerCountry	2 long text	no (in case of tradeType E and D yes)	Country code of the sender/seller	HU

loadLocation	element	no (in case of tradeType E and D yes)	Address of loading	Budapest Ipartelep u 1.
saveLoadLocation	xs:boolean	no, default: false	In case of yes, the load location is saved among favorites, when it still does not exist.	true
unloadLocation	element	no (in case of tradeType I and D yes)	Address of unloading	B a K a á utca 1.

2.3.2.5 COUNTRY LIST

At the address data and the country fields only the following country codes can be given:

- < AT Austria
- < BE Belgium
- < BG Bulgaria
- < CY Cyprus
- < CZ Czech Republic
- < DK Denmark
- < GB United Kingdom
- < EE Estonia
- <

in kgs. Max 9 long whole number.

an increase of value, the risk assurance is increased accordingly, and if there is no sufficient assurance

2.6.2

between 1-1000 1000

- ◁ msg: Text description of the result defined by the reasonCode. More accurate description of the error. In case of successful execution not to be filled in, can be omitted.

3.5.1 ReasonCode Enumerated types

<

4.3 ACCESSIBILITY OF THE TEST SYSTEM (Old